

PRO-FILL 601

FAST DRYING ACRYLIC PASTE



TECHNICAL DATA SHEET

PRO-FILL 601 is a one component filling paste, which dries very fast and produces a very smooth and hard finish. For interior and exterior use, above and below the waterline. Use to fill very small imperfections only, e.g. pinholes, scratches, blemishes and to make last minute improvements to the surface before top coating. It can be used on any primed or filled surface.

Application method

Apply using metal or plastic spreader.

Recommended usage

Mainly applied to primed surfaces before top coating.

Features

- 1 component,
- very easy to fair, in just 25 minutes,
- for use above and below the waterline,
- white colour makes filled areas easy to cover.

Limitations

- Use only for the smallest of imperfections, up to 0.5 mm deep,
- must be used as part of a system which includes a primer underneath and a top coat above it.

Product data

PRO-FILL 601: Product data	
Colour	white
Viscosity, approx., cP	10,000
Specific weight, kg/lt	1.54
Volume solids, %	51
Shelf life (in controlled environment), years	1
Packaging, ml	100



TECHNICAL DATA SHEET

PRO-FILL 601: Drying time			
	10 °C	20 °C	30 °C
Pot life, secs	90	60	45
Sandable, mins	25	25	25

Preparation & application

Application should be carried out in optimal conditions, namely temperature in the range of 10-35 °C (ambient, substrate and product) and normal humidity levels.

The application surface must be primed and clean, free of dust, salt, water, grease, oil, wax, silicone, rust and other contaminants deposited over time or during the repair process.

The recommended way of cleaning is by dry cloth assisted by vacuum dust extractor or compressed air (free of compressor oils). Use a large cloth, apply very lightly and change sides continuously so as to remove dust instead of pressing it on the substrate. Avoid using wet or waxed tissues. As an alternative, if necessary, use PRO-CLEAN IPA, the fast drying, residue free, isopropyl alcohol solvent.

Keep in mind that during application you are constrained by the very small pot-life of the product. Only take small quantities out of the container, matching the amount of product that you will be able to apply within the pot life window, which is often less than a minute. Apply very thin layers with a spreader in one or two directions. Allow layers to feather around the imperfections to be filled. These will be easily levelled when faired.

Fair very lightly with whatever grade you are preparing the rest of the surface for overcoating.

Clean with dry cloth only, no solvents.

Inspect to see if the required level of filling has been achieved. More than one application may be needed. Note that PRO-FILL 601, contrary to epoxy fillers, shrinks during drying. To achieve thickness, go for multiple applications not thicker layers.

You are advised to first test the product, surface preparation and ambient conditions on a non-critical part of the application surface before proceeding with the full repair.

PRO-FILL 601

FAST DRYING ACRYLIC PASTE

TECHNICAL DATA SHEET



Packaging

100 ml.

Storage & shelf life

At least 12 months from the date of manufacture in the original sealed container. Store away from excessive heat and humidity.

Quality control

PRO-FILL 601 is produced under ISO 9001/14001/45001.

Safety

Use in well ventilated spaces away from sparks or open flames. Follow personal safety guidelines, including the use of proper mask, gloves and protective clothing. Avoid physical contact with the uncured substance.

The information provided in this Technical Data Sheet is to be used as a guideline only. It represents no warranty of any kind. None of the information, instructions and specifications, published by Navic, in writing or in any other form, are to be considered as binding in any way or towards any parties, nor do they relieve interested parties from subjecting the product to an adequate examination of its suitability. In no case will Navic be held responsible for any damage of any nature resulting from the use of or reliance upon information or the product to which information refers. Navic reserves the right to change at any time the properties of its products. Please refer to the latest version of our Technical Data Sheet available on our website, navic-chemicals.com.